

CLAIM AMENDMENTS:

Please cancel Claims 2-7, and amend Claim 1 as follows:

1. (currently amended) A missile or aircraft comprising
 - a. an afterbody and a forebody;
 - b. at least one flow effector on the missile or aircraft forebody;
 - c. at least one sensors each having a signal, the at least one sensor being positioned to detect flow separation or side forces on the missile or aircraft forebody; and
 - d. a closed loop control system;

wherein the closed loop control system is used for activating and deactivating the at least one flow effector based on at least in part the signal of the at least one sensor to create commanded side forces on the missile or aircraft forebody.

2. (cancelled)
3. (cancelled)
4. (cancelled)
5. (cancelled)
6. (cancelled)
7. (cancelled)

8. (previously presented) A flow control system for a missile or aircraft forebody comprising

- a. at least one flow effectors;
- b. at least one sensor having a signal, the at least one sensor being positioned to detect flow separation or side forces on the missile or aircraft forebody; and
- c. an inertial measurement unit having an output;
- d. a closed loop control system;

wherein the closed loop control system is used for activating and deactivating the at least one flow effector based on at least in part the signal of the at least one sensor and the output of the inertial measurement unit.

9. (previously presented) The flow control system in claim 8, comprising at least four flow effectors.

10. (previously presented) The flow control system in claim 8, comprising at least six flow effectors wherein the at least six flow effectors are positioned and separated substantially equi-distantly about a center of the forebody of the missile or aircraft.

11. (original) The flow control system in claim 8, wherein the flow effectors are capable of being activated and deactivated at frequencies of at least 1 Hz.

12. (original) The flow control system in claim 8, wherein the flow effectors are capable of being activated and deactivated at frequencies of at least 20 Hz.

13. (original) The flow control system in claim 8, wherein the closed loop control system activates and deactivates the at least one flow effector to create commanded side

forces on the missile or aircraft forebody.

14. (original) The flow control system in claim 12, wherein the closed loop control system activates and deactivates the at least one flow effector to create additional side forces on the missile or aircraft forebody.

15. (previously presented) A method of maneuvering a missile or aircraft forebody comprising the steps of

- a. estimating or determining side forces on a missile or an aircraft forebody based at least in part on a signal from at least one sensor, the at least one sensor being positioned to estimate or determine side forces on the missile or aircraft forebody; the missile or aircraft forebody further comprising at least one flow effector and a closed loop control system for controlling the at least one flow effectors;
- b. activating the at least one flow effector to change the side forces by activation of the at least one flow effector with the closed loop controller based on at least in part the signal of the at least sensor; and
- c. re-estimating or determining side forces on the missile or aircraft forebody based at least in part on a signal from the at least one sensor; and
- d. deactivating the at least one flow effector in response to changed side forces.

16. (previously presented) The method of maneuvering in claim 15, wherein the at least one flow effector is activated by oscillating the at least one flow effector.

17. (previously presented) The method of maneuvering in claim 15, wherein the missile or aircraft forebody comprises at least six flow effectors wherein the at least six flow effectors are positioned and separated substantially equi-distantly about a center of the forebody of the missile or aircraft.

18. (previously presented) The method of maneuvering in claim 15, wherein the forebody of the missile or aircraft is designed with asymmetries in the forebody.

19. (previously presented) The method of maneuvering in claim 15, wherein the at least one flow effector is only activated at angles of attack of the missile or aircraft forebody of between about 20 to about 60 degrees.

20. (previously presented) The method of maneuvering in claim 15, wherein the at least one flow effector is a deployable flow effector.